

Usage: enscript [OPTION]... [FILE]...

Mandatory arguments to long options are mandatory for short options too.

```

-#                an alias for option -n, --copies
-1                same as --columns=1
-2                same as --columns=2
  --columns=NUM   specify the number of columns per page
-a, --pages=PAGES specify which pages are printed
-A, --file-align=ALIGN align separate input files to ALIGN
-b, --header=HEADER set page header
-B, --no-header   no page headers
-c, --truncate-lines cut long lines (default is to wrap)
-C[START], --line-numbers[=START]
                  precede each line with its line number
-d                an alias for option --printer
-D, --setpagedevice=KEY[:VALUE]
                  pass a page device definition to output
-e[CHAR], --escapes[=CHAR] enable special escape interpretation
-E[LANG], --highlight[=LANG] highlight source code
-f, --font=NAME   use font NAME for body text
-F, --header-font=NAME use font NAME for header texts
-g, --print-anyway nothing (compatibility option)
-G                same as --fancy-header
  --fancy-header[=NAME] select fancy page header
-h, --no-job-header suppress the job header page
-H[NUM], --highlight-bars[=NUM] specify how high highlight bars are
-i, --indent=NUM  set line indent to NUM characters
-I, --filter=CMD  read input files through input filter CMD
-j, --borders     print borders around columns
-J,              an alias for option --title
-k, --page-prefeed enable page prefeed
-K, --no-page-prefeed disable page prefeed
-l, --lineprinter simulate lineprinter, this is an alias for:
                  --lines-per-page=66, --no-header, --portrait,
                  --columns=1
-L, --lines-per-page=NUM specify how many lines are printed on each page
-m, --mail        send mail upon completion
-M, --media=NAME  use output media NAME
-n, --copies=NUM  print NUM copies of each page
-N, --newline=NL  select the newline character. Possible
                  values for NL are: n ('\n') and r ('\r').
-o                an alias for option --output
-O, --missing-characters list missing characters
-p, --output=FILE leave output to file FILE. If FILE is '-',
                  leave output to stdout.
-P, --printer=NAME print output to printer NAME
-q, --quiet, --silent be really quiet
-r, --landscape   print in landscape mode
-R, --portrait    print in portrait mode
-s, --baselineskip=NUM set baselineskip to NUM
-S, --statusdict=KEY[:VALUE]
                  pass a statusdict definition to the output
-t, --title=TITLE set banner page's job title to TITLE. Option
                  sets also the name of the input file stdin.
-T, --tabsize=NUM set tabulator size to NUM
-u[TEXT], --underlay[=TEXT] print TEXT under every page
-U, --nup=NUM     print NUM logical pages on each output page
-v, --verbose     tell what we are doing
-V, --version     print version number
-w, --language=LANG set output language to LANG
-W, --options=APP,OPTION pass option OPTION to helper application APP
-X, --encoding=NAME use input encoding NAME
-z, --no-formfeed do not interpret form feed characters
-Z, --pass-through pass through PostScript and PCL files
                  without any modifications

```

Long-only options:

```

--color[=bool]    create colour outputs with states
--continuous-page-numbers count page numbers across input files. Don't
                  restart numbering at beginning of each file.

```

```
--download-font=NAME      download font NAME
--extended-return-values  enable extended return values
--filter-stdin=NAME       specify how stdin is shown to the input filter
--footer=FOOTER           set page footer
--h-column-height=HEIGHT  set the horizontal column height to HEIGHT
--help                    print this help and exit
--help-highlight          describe all supported --highlight languages
                           and file formats
--highlight-bar-gray=NUM  print highlight bars with grey NUM (0 - 1)
--list-media              list names of all known media
--margins=LEFT:RIGHT:TOP:BOTTOM
                           adjust page marginals
--mark-wrapped-lines[STYLE]
                           mark wrapped lines in the output with STYLE
--non-printable-format=FMT
                           specify how non-printable chars are printed
--nup-columnwise          layout pages in the N-up printing columnwise
--nup-xpad=NUM            set the page x-padding of N-up printing to NUM
--nup-ypad=NUM            set the page y-padding of N-up printing to NUM
--page-label-format=FMT  set page label format to FMT
--ps-level=LEVEL         set the PostScript language level that enscript
                           should use
--printer-options=OPTIONS
                           pass extra options to the printer command
--rotate-even-pages      rotate even-numbered pages 180 degrees
--slice=NUM              print vertical slice NUM
--style=STYLE            use highlight style STYLE
--swap-even-page-margins  swap left and right side margins for each even
                           numbered page
--toc                     print table of contents
--ul-angle=ANGLE         set underlay text's angle to ANGLE
--ul-font=NAME           print underlays with font NAME
--ul-gray=NUM            print underlays with grey value NUM
--ul-position=POS        set underlay's starting position to POS
--ul-style=STYLE         print underlays with style STYLE
--word-wrap              wrap long lines from word boundaries
```

Report bugs to <bug-enscript@gnu.org>.